

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 27-Mar-13 08:45	FS — 10	BN 879 SL 102/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30				
DL -29 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1170				
TS 12 TB 8.0		B PD: 10007-075 T1 9.5 2L/C 4.7 VA 1000 UE 1022 LP 0.00 ft LI 1.0		

ACCEPT SQ-OFF FL-OFF PR-OFF	VMX= 3.9 FMX= 60 AMX= 139
	EMX= 0.2 MEX= 117 FUP= 1.00
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable
	SERIAL NUMBER: 10007
	CALIBRATION FACTOR: 1170 g/v
	PAK (*5000): DATE: 27-MAR-13
PDA OPERATOR: <i>[Signature]</i>	
OP: alex [ver:4.05]	
AT: PIEZOELECTRIC	

contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE