

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 03-Mar-04 16:40		FS — 10	BN 340 SL 2509/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 995		TS 12 E B PD: 10823 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1024 LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

VMX= 5.6 FMX= 87 AMX= 189
 EMX= 0.5 MEX= 170 FUP= 1.01

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10823

CALIBRATION FACTOR: 995 G/V

PAK <3000>: DATE: 03-Mar-04

PDA OPERATOR: Fred Phoebe

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->