

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 03-Mar-04 17:00		FS — 10	BN 384 SL 2509/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN ~~KIPS~~ 30.3 FR 20000 MB 30					
DL -41 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1015					
TS 12 TB 8.0		E B PD: 10824 T1 9.7 2L/C 4.7 VA 1000 UE 1024 LP 0.00 ft LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

UMX= 5.4 FMX= 84 AMX= 189
 EMX= 0.4 MEX= 164 FVP= 1.01

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10824

CALIBRATION FACTOR: 1015 G/V

PAK <<5000>>: DATE: 03-Mar-04

PDA OPERATOR: Fred Blum

OP: FRED [ver:4.05]

>AT:PIEZOELECTRIC<