

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 03-Mar-04 16:38		FS — 10	BN 333 SL 2509/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30					
DL -40 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1020		TS 12 TB 8.0	E B T1 9.6	PD: 10832 2L/C 4.7	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 5.3 FMX= 81 AMX= 189 EMX= 0.4 MEX= 158 FUP= 1.00
------------------------------------	--



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10832

CALIBRATION FACTOR: 1020 G/V

PAK <5000>: DATE: 03-MW-04

PDA OPERATOR: Fred Phasini

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

[AT:PIEZOELECTRIC->