

File Dynamics 29-Aug-11 14:35 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30 DL -43 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1015	FS 10 BN 708 SL 3200/ 3440/ 2 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 TB 8.0 T1 9.6 B PD: 10835-060 2L/C 4.7 UA 1000 LP 0.00 ft LI 1.0
---	--

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.0 FMX= 62 AMX= 149
 EMX= 0.2 MEX= 121 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 10835
 CALIBRATION FACTOR: 1015 g/v
 PAK (*5000): DATE: 29-AUG-11
 PDA OPERATOR: *[Signature]*