

| | | | | | | | |
|--|------------|----------------------------|----------------------|--------------------------|------------------------------------|---------|----------------------|
| File Dynamics 14-Jan-10 11:02 | FS — 10 | BN 97 SL 2839/ 3440/ 99 | PJ: sn PN: HOPBAR | TG F2 -- US A2 F2 3.3 | | | |
| LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s | | | | | | | |
| JC 0.40 FM 1.00 UM 1.00 | | | | | | | |
| EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30 | | | | | | | |
| DL -43 UT -1 PK 1 TM-PEAK | | | | | | | |
| F1 500 F2 213 A1 999 A2 1035 | | | | | | | |
| TS 12 TB 8.0 | | | | | B PD: 10838-060 T1 9.2 2L/C 4.7 | VA 1000 | LP 0.00 ft LI 1.0 |

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.1 FMX= 64 AMX= 100
EMX= 0.3 MEX= 125 FUP= 0.97



contact File Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10838

CALIBRATION FACTOR: 1035 G/v

PAK (*5000): DATE: 14-Jan-10

PDA OPERATOR: Dale D. Small

<-AT:PIEZORESISTIVE

OP: dale [ver:4.05]

AT:PIEZOELECTRIC->