

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 20-Sep-12 09:37		FS — 10	BN 1011 SL 3305/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPSx0.1 FR 20000 MB 30 DL -35 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1010	TS 12 B PD: 11270-060 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 VA 1000 VE 1022 LI 1.0				

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

VMX= 4.0 FMX= 62 AMX= 149
 EMX= 0.2 MEX= 121 FVP= 1.00

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: 11270

CALIBRATION FACTOR: 1010 G/v

PAK (*5000): DATE: 20-SEP-12

PDA OPERATOR: Alex

OP: ALEX [ver:4.05]

>AT:PIEZOELECTRIC->