

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 08-Jul-04 07:23		FS —	BN 640	PJ:	TG F2 -- US
		10	SL 2585/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE	39.6 ft				
AR	1.7 in2				
EM	30000 Ksi				
SP	0.492 K/ft3				
WS	16810 ft/s				
WC	16862 ft/s				
JC	0.40				
FM	1.00				
UM	1.00				
EA/C 30.3 Ks/ft					
UN KIPS=0.1					
FR 20000 MB 30					
DL -42					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 995					
TS 12		B PD: 11271		LP 0.00 ft	
TB 7.0		T1 9.6		2L/C 4.7 UA 1000 UE 1024 LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 5.0 FMX= 77 AMX= 169
 EMX= 0.4 MEX= 150 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11271

CALIBRATION FACTOR: 995 G/V

PAK (←3000): DATE: 08-JUL-04

PDA OPERATOR: Fred Khazani

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

>-AT:PIEZOELECTRIC>