

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

|                                                                                              |  |                                                                         |                             |                   |                          |
|----------------------------------------------------------------------------------------------|--|-------------------------------------------------------------------------|-----------------------------|-------------------|--------------------------|
| <b>Pile Dynamics</b><br><b>14-Jun-04 13:02</b>                                               |  | FS —<br>10                                                              | BN 232<br>SL 2528/ 3440/ 99 | PJ:<br>PN: HOPBAR | TG F2 -- US<br>A2 F2 3.3 |
| LE 39.6 ft<br>AR 1.7 in2<br>EM 30000 Ksi<br>SP 0.492 K/ft3<br>WS 16810 ft/s<br>MC 16862 ft/s |  |                                                                         |                             |                   |                          |
| JC 0.40<br>FM 1.00<br>UM 1.00                                                                |  |                                                                         |                             |                   |                          |
| EA/C 30.3 Ks/ft<br>UN <del>KIPS/IN</del><br>FR 20000 MB 30                                   |  |                                                                         |                             |                   |                          |
| DL -38<br>UT -1<br>PK 1 TM-PEAK                                                              |  |                                                                         |                             |                   |                          |
| F1 500<br>F2 213<br>A1 999<br>A2 1070                                                        |  |                                                                         |                             |                   |                          |
| TS 12<br>TB 8.0                                                                              |  | B PD: 11274<br>T1 9.5 2L/C 4.7 UA 1000 <b>UE 1024</b> LP 0.00 ft LI 1.0 |                             |                   |                          |

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

UMX= 4.6 FMX= 70 AMX= 149  
 EMX= 0.3 MEX= 137 FUP= 1.00

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: 11274

CALIBRATION FACTOR: 1070 G/V

PAK &lt;5000&gt;:

DATE: 14-Jun-04

PDA OPERATOR:

Fred Iver

&lt;-AT:PIEZORESISTIVE

OP: Fred Iver:4.05]

[AT:PIEZOELECTRIC-&gt;