

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 14-Jun-04 13:08		FS —	BN 242	PJ:	TG F2 -- US
		10	SL 2528/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE	39.6 ft				
AR	1.7 in2				
EM	30000 Ksi				
SP	0.492 K/ft3				
WS	16810 ft/s				
WC	16862 ft/s				
JC	0.40				
FM	1.00				
UM	1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -40					
UT -1					
PK 1	TM-PEAK				
F1 500					
F2 213					
A1 999					
A2 1030					
		TS 12	B	PD: 11275	LP 0.00 ft
		TB 8.0	T1 9.5	2L/C 4.7	UA 1000 UE 1024 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.7 FMX= 74 AMX= 149
 EMX= 0.3 MEX= 145 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11275

CALIBRATION FACTOR: 1030 G/V

PAK <X5000>: DATE: 14-Jun-04

PDA OPERATOR: Fred Iverson

<-AT:PIEZORESISTIVE

OP: Fred Iverson:4.051

>AT:PIEZOELECTRIC<