

QBTA: ON IALT-F1/BB=601

Pile Dynamics, Inc.

DPF

Pile Dynamics 14-Jun-04 13:14		FS — 10	BN 257 SL 2528/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN ~~KIPS~~ 0.1 FR 20000 MB 30 DL -36 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1035		TS 12 B PD: 11276 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 VA 1000 VE 1024 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		UMX= 4.8 FMX= 75 AMX= 159 EMX= 0.4 MEX= 147 FUP= 1.00			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11276 CALIBRATION FACTOR: 1035 G/V PAK (<5000>): DATE: 14-Jun-04 PDA OPERATOR: Fred [signature]			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		<-AT:PIEZORESISTIVE OP: Fred [ver:4.05] AT:PIEZOELECTRIC->			