

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 01-Dec-04 14:20		FS —	BN 288	PJ:	TG F2 -- US
		10	SL 2539/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16862 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL -44					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 1025					
TS 12		B PD: 12895-060	LP 0.00 ft		
TB 8.0		T1 9.5 2L/C 4.7 VA 1000 VE 1010	LI 1.0		

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

VMX= 5.4 FMX= 84 AMX= 189
EMX= 0.4 MEX= 164 FVP= 1.00

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: 12895

CALIBRATION FACTOR: 1025 G/V

PAK <#8888>: DATE: 01-Dec-04

PDA OPERATOR: Fred Hussein

<-AT:PIEZORESISTIVE

OP: fred [ver:4.05]

[AT:PIEZOELECTRIC->