

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

File Dynamics 16-Nov-04 11:37		FS — 10	BN 508 SL 2540/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -43 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1030		TS 12 B PD: 12901-060 LP 0.00 ft TB 7.0 T1 9.3 2L/C 4.7 VA 1000 UE 1024 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.2 FMX= 66 AMX= 129 EMX= 0.3 MEX= 129 FVP= 1.01			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 12901 CALIBRATION FACTOR: 1030 G/V PAK ←#5000→: DATE: 16-Nov-04 PDA OPERATOR: Fred Hussari			
contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		←-AT:PIEZORESISTIVE OP: FRED [ver:4.05] AT:PIEZOELECTRIC->			