

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 06-Sep-10 12:57	FS — 10	BN 683 SL 2893/ 3440/ 2	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -40 UT -48 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 510						
TS 12 TB 8.0					B PD: 12903.060 T1 9.6 2L/C 4.7	LP 0.00 ft LI 1.0
UA 1000 UE 1022						
VE 1022						
VE 1022						
VE 1022						

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 2.1 FMX= 62 AMX= 139
 EMX= 0.4 MEX= 121 FVP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 12903

CALIBRATION FACTOR: 1020 G/V

PAK (*5000): DATE: 07-SEP-10

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->