

QBT: ON IALT-F1/BB=601

Pile Dynamics, Inc.

DPF

Pile Dynamics 23-Feb-07 13:27		FS — 10	BN 28 SL 2585/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPSx0.1 FR 20000 MB 30					
DL -41 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1055		TS 12 TB 8.0	B PD: 13622-060 T1 9.5 2L/C 4.7	VA 1000	LP 0.00 ft LI 1.0

	UMX= 4.5 FMX= 69 AMX= 159
	EMX= 0.3 MEX= 135 FUP= 1.00
	ACCEPT SQ-OFF FL-OFF PR-OFF SERIAL NUMBER: 13622 CALIBRATION FACTOR: 105561V PAK-(*5000)- DATE: 23-FEB-07 PDA OPERATOR: <i>[Signature]</i> OP: alex lver:4.051
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	
<-AT:PIEZORESISTIVE AT:PIEZOELECTRIC->	