

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 26-Feb-05 13:45		FS —	BN 504	PJ:	TG F2 -- US
		10	SL 2526/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16862 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1		TB 8.0 T1 9.6 2L/C 4.7 VA 1000 VE 1022 LI 1.0			
FR 20000 MB 30					
DL -40					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 1055					

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

VMX= 5.0 FMX= 75 AMX= 189
EMX= 0.3 MEX= 147 FVP= 1.01

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: 13631

CALIBRATION FACTOR: 1055 G/V

PAK (X5000): DATE: 26-Feb-05

PDA OPERATOR: FJH Hulsein

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

[AT:PIEZOELECTRIC->