

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 02-Mar-06 19:02		FS —	BN 151 1433 1	PJ:	TG F2 -- US
		10	SL 2672/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE	39.6 ft				
AR	1.7 in2				
EM	30000 Ksi				
SP	0.492 K/ft3				
WS	16810 ft/s				
WC	16862 ft/s				
JC	0.40				
FM	1.00				
UM	1.00				
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL	-42				
UT	-1				
PK	1 TM-PEAK				
F1	500				
F2	213				
A1	999				
A2	1155				
		TS 12	B	PD: 18748-060	LP 0.00 ft
		TB 8.0	T1 9.5	2L/C 4.7 VA 200	VE 1022 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.7 FMX= 72 AMX= 149
EMX= 0.3 MEX= 141 FVP= 0.98



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 18748

CALIBRATION FACTOR: 1155 G/V

PAK (*5000): DATE: 02-Mar-06

PDA OPERATOR: JFM

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->