

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 14-Mar-06 19:59		FS — 10	BN1612 2894 SL 2829/ 3440/ 99	1 PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -41 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1010					
		TS 12 TB 8.0	B PD: 18766-060 T1 9.6 2L/C 4.7	VA 1000 VE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 5.1 FMX= 80 AMX= 199 EMX= 0.4 MEX= 156 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 18766 CALIBRATION FACTOR: 1010 G/V PAK (*5000): PDA OPERATOR: <i>[Signature]</i> DATE: 14-MAR-06
---	---

<-AT:PIEZORESISTIVE

OP: FRED Iver:4.051

AT:PIEZOELECTRIC->