

DPF

Pile Dynamics 10-Feb-09 10:07 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPSx0.1 FR 20000 MB 30 DL -33 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 970	FS — 10 BN 192 SL 2744/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 A2 F2 -- US 3.3	
---	---	--

TS 12	B	PD: 18837-060	LP 0.00 ft
TB 8.0	T1 9.5	2L/C 4.7 VA 1000	LI 1.0

VMX= 3.9	FMX= 60	AMX= 149
EMX= 0.2	MEX= 117	FVP= 1.00

	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 18837 CALIBRATION FACTOR: 9706/v *PAK (*5080): PDA OPERATOR: <i>[Signature]</i>
--	---

contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	DATE: 10-FEB-09
--	-----------------

<-AT:PIEZORESISTIVE
OP: alex lver:4.051
AT:PIEZOELECTRIC->