

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Nov-11 14:03		FS — 10	BN 1511 SL 3281/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30 DL -26 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1065		TS 12 B PD: 18954-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 VA 1000 UE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.2 FMX= 63 AMX= 169 EMX= 0.3 MEX= 123 FUP= 0.97			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 18954 CALIBRATION FACTOR: 1065 G/v PAK (*5000): DATE: 21-NOV-11 PDA OPERATOR: <i>Dan B...</i>			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		OP: dale [ver:4.05]			

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->