

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 06-Apr-06 11:08		FS —	BN 274	PJ:	TG F2 -- US
		10	SL 2607/ 3440/ 2	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16862 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL -42					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 985					
TS 12		B PD: 18958-060	LP 0.00 ft	EI	
TB 7.0		T1 9.5	2L/C 4.7	VA 1000	UE 1022 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.6 FMX= 73 AMX= 149
 EMX= 0.3 MEX= 143 FVP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 18958

CALIBRATION FACTOR: 985 G/V

PAK: (X5000): DATE: 06-Apr-06

PDA OPERATOR: *OTM*

<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->