

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 02-Oct-13 07:36		FS — 10	BN 999 SL 173/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -40 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 995					
TS 12 TB 8.0		B PD: 19157-060 T1 9.5 2L/C 4.7 VA 1000 VE 1022 LP 0.00 ft LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.1 FMX= 63 AMX= 139
 EMX= 0.2 MEX= 123 FVP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 19157

CALIBRATION FACTOR: 995 G/v

PAK (*5000) DATE: 02-OCT-13

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->