

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 07-Aug-09 07:44		FS — 10	BN 230 SL 2808/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -37 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 945	TS 12 TB 8.0	B PD: 19292-060 T1 9.5 2L/C 4.7	VA 1000	VE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

UMX= 4.1 FMX= 64 AMX= 139
EMX= 0.3 MEX= 125 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 19292

CALIBRATION FACTOR: 945 G/v

PAK (#5060): DATE: 7-Aug-09

PDA OPERATOR: Dale Brunell

<-AT:PIEZORESISTIVE

OP: dale Iver:4.051

AT:PIEZOELECTRIC->