

QBTA: ON [ALT-F1/BB=601]

Pile Dynamics, Inc.

DPF

File Dynamics 15-Jun-14 01:29		FS — 10	BN 1170 SL 288/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30					
DL -42 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1015					
TS 12 TB 8.0		B PD: 19294-060 T1 9.4 2L/C 4.7 VA 1000 VE 1022	LP 0.00 ft LI 1.0		

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

VMX= 4.4 FMX= 68 AMX= 139
EMX= 0.3 MEX= 133 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 19294

CALIBRATION FACTOR: 1015 %

PAK (*5000): DATE: 15 JUNE 14

PDA OPERATOR: M. Wray

OP: laine [ver:4.05]

AT:PIEZOELECTRIC->