

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

File Dynamics 12-Feb-09 13:43		FS — 10	BN 711 SL 2763/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1000		TS 12 B PD: 19305-060 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 3.6 FMX= 58 AMX= 129 EMX= 0.2 MEX= 113 FVP= 0.97			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 19305 CALIBRATION FACTOR: 1000 G/V PAK (*5000): DATE: 12-FEB-09 PDA OPERATOR: <i>[Signature]</i>			
contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		←-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC→			