

QBTA: ON [ALT-F1/BB=60]


Pile Dynamics, Inc.

DPF

File Dynamics  
2018-06-07 07:16FS —  
10BN 3773  
SL 1705/ 3440/ 2PJ:  
PN: HOPBARTG F2 -- US  
A2 F2 3.3LE 17.0 ft  
AR 1.7 in2  
EM 30000 Ksi  
SP 0.492 K/ft3  
WS 16810 ft/s  
WC 7312 ft/sJC 0.40  
FM 1.00  
UM 1.00EA/C 30.3 Ks/ft  
UN KIPS±0.1  
FR 20000 MB 90DL -43  
UT -1 IP 0.00  
PK 1 TM-PEAKF1 500  
F2 213  
A1 999  
A2 1000TS 12 E B PD: 19308-060 LP 0.00 ft  
TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1024 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



&lt;-AT:PIEZORESISTIVE

VMX= 8.4 FMX= 61 AMX= 120  
EMX= 0.3 MEX= 119 FVP= 0.99

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 19308

CALIBRATION FACTOR: 1000 %

PAK (\*5000): DATE: 7JUN618

PDA OPERATOR: [Signature]

OP: laine [ver:5.01]

AT:PIEZOELECTRIC-&gt;