

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 08-Jun-09 11:26		FS — 10	BN 983 SL 2813/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US 02 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -27 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1005		TS 12 B PD: 19513-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 VA 1000 UE 1022 LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.0 FMX= 61 AMX= 139 EMX= 0.2 MEX= 119 FVP= 1.00
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 19513 CALIBRATION FACTOR: 1005 G/v PAK (*5000) DATE: 08-JUN-09 PDA OPERATOR: <i>[Signature]</i>
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	<-AT:PIEZORESISTIVE OP: alex Iver:4.051 AT:PIEZOELECTRIC->