

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 15-May-06 09:46		FS — 10	BN 683 SL 2667/ 3440/ 2	PJ: CAL TEST PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -40 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1120	TS 12 TB 8.0	B PD: 19614-060 T1 9.6 2L/C 4.7	UA 1000	UE 1022	LP 0.00 ft LI 1.0

	ACCEPT SQ-OFF FL-OFF PR-OFF UMX= 5.1 FMX= 80 AMX= 199 EMX= 0.4 MEX= 156 FVP= 1.00
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 19614 CALIBRATION FACTOR: 1120 GLV PAK (*5880): DATE: 15-May-06 PDA OPERATOR: Fred Hein
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	OP: fred [ver:4.05]

<-AT:PIEZORESISTIVE

[AT:PIEZOELECTRIC->