

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 04-Mar-10 15:06		FS — BN 91 SL 2867/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30				
DL -42 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 999				
TS 12 TB 7.0		B PD: 19672-60 T1 9.1 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0	
ACCEPT SQ-OFF FL-OFF PR-OFF		UMX= 3.5 FMX= 55 AMX= 80 EMX= 0.2 MEX= 107 FVP= 0.98		
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable		
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		SERIAL NUMBER: 19672 CALIBRATION FACTOR: 999 G/V PAK (*5000): DATE: 4/10/10 PDA OPERATOR: wfb		
<-AT:PIEZORESISTIVE		OP: DAVE [ver:4.05]		
		[AT:PIEZOELECTRIC->		