

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 04-Mar-10 15:08		FS —	BN 96	PJ: sn	TG F2 -- US
		10	SL 2867/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16862 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL -42					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 1025					
TS 12		B PD: 19677-60		LP 0.00 ft	
TB 7.0		T1 9.2		LI 1.0	
		2L/C 4.7		VA 1000	
		UE 1022			

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 3.9 FMX= 62 AMX= 100
EMX= 0.2 MEX= 121 FUP= 1.00



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 19677

CALIBRATION FACTOR: 1025618

PAK (*5000): DATE: 4 Mar, 10

PDA OPERATOR: D/66

<-AT:PIEZORESISTIVE

OP: DAVE [ver:4.05]

AT:PIEZOELECTRIC->