

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 23-May-16 05:05		FS — 10	BN 228 SL 449/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPSx0.1 FR 20000 MB 30					
DL -42 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 980					
TS 12 TB 8.0		B PD: 19911-060 T1 9.5 2L/C 4.7 VA 1000 UE 1022 LP 0.00 ft LI 1.0			

	UMX= 4.5 FMX= 69 AMX= 129
	EMX= 0.3 MEX= 135 FVP= 1.00
	ACCEPT SQ-OFF FL-OFF PR-OFF
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	SERIAL NUMBER: 19911
	CALIBRATION FACTOR: 980%
	PAK (*5000): DATE:
	PDA OPERATOR: <i>Ja</i>
<-AT:PIEZORESISTIVE OP: laine [ver:4.05] AT:PIEZOELECTRIC->	