

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 01-Jun-06 11:31	FS — 10	BN 93 SL 2588/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30						
DL -29 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1025						
TS 12 TB 8.0					B PD: 19912-060 T1 9.6 2L/C 4.7	LP 0.00 ft LI 1.0
VE 1022						
UA 1000						
UE 1022						
LI 1.0						

	UMx= 4.4 FMx= 69 AMx= 169 EMx= 0.3 MEx= 135 FUP= 1.00
	ACCEPT SQ-OFF FL-OFF PR-OFF
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 19912 CALIBRATION FACTOR: 1025 G/V PAR (*5000): _____ DATE: 01-Jun-06 PDA OPERATOR: <i>Fred</i>
<-AT:PIEZORESISTIVE	OP: fred [ver:4.05]
<AT:PIEZOELECTRIC>	