

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 10-Oct-06 10:10		FS — 10	BN 47 SL 2585/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -26 UT 0 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1025		TS 12 TB 8.0	B PD: 19989-060 T1 9.6 2L/C 4.7 VA 1000	LP 0.00 ft LI 1.0	UE 1022

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

VMX= 3.9 FMX= 59 AMX= 139
EMX= 0.2 MEX= 115 FVP= 0.97

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 19989

CALIBRATION FACTOR: 1025 G/V

PAK (*5000): DATE: 10-OCT-06

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex Iver:4.05

[AT:PIEZOELECTRIC->