

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 10-Oct-06 10:37	FS — 10	BN 115 SL 2586/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30				
DL -25 UT 0 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1070				
TS 12 TB 8.0		B PD: 19998-060 T1 9.6 2L/C 4.7 VA 1000 UE 1022 LP 0.00 ft LI 1.0		

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions

tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

VMX= 4.2 FMX= 63 AMX= 159
EMX= 0.3 MEX= 123 FVP= 0.94

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: 19998

CALIBRATION FACTOR: 1070 G/V

PAK (*5000):

DATE: 10-OCT-06

PDA OPERATOR:

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->