

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 10-Oct-06 10:25		FS — 10	BN 84 SL 2585/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -25 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1000		TS 12 TB 8.0	B PD: 20013-060 T1 9.6 2L/C 4.7	VA 1000 UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.1 FMX= 64 AMX= 159
	EMX= 0.3 MEX= 125 FUP= 0.97
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable
	SERIAL NUMBER: 20013
	CALIBRATION FACTOR: 1000 g/V
	RAK (*5000): DATE: 10-06T-06
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	PDA OPERATOR: <i>[Signature]</i>
<-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC->	