

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 15-Aug-06 15:20		FS — 10	BN 117 SL 2593/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 980		TS 12 B PD: 20075-060 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 5.2 FMX= 82 AMX= 189 EMX= 0.4 MEX= 160 FVP= 0.99			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 20075 CALIBRATION FACTOR: 980 G/V RAK (*5000): DATE: 15-AUG-06 PDA OPERATOR: <i>[Signature]</i>			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		<-AT:PIEZORESISTIVE OP: alex lver:4.051 AT:PIEZOELECTRIC->			