

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 16-Mar-12 14:03		FS — 10	BN 5675 SL 246/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS/ft FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 990		TS 12 B PD: 20077-060 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 VA 1000 UE 1022 LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER:

20077

CALIBRATION FACTOR:

990 g/v

PAK (*5000):

DATE: 16-MAR-12

PDA OPERATOR:

<-AT:PIEZORESISTIVE

OP: ALEX [ver:4.05]

AT:PIEZOELECTRIC->