

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 30-Mar-14 08:09		FS —	BN 625	PJ:	TG F2 -- US
		10	SL 211/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16684 ft/s					
JC 0.40					
FM 1.00					
VM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL -39					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 1045					
		TS 12	B	PD: 20084-060	LP 0.00 ft
		TB 8.0	T1 9.4	2L/C 4.8	VA 1000
				UE 1022	LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

VMX= 4.4 FMX= 67 AMX= 139
EMX= 0.3 MEX= 131 FVP= 1.01

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 20084

CALIBRATION FACTOR: 1045 %

PAK (*5000): DATE: 2 APR 14

PDA OPERATOR: M. Wang

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

[AT:PIEZOELECTRIC->