

QBTA: ON [ALT-F1/BB=601

Pile Dynamics, Inc.

DPF

Pile Dynamics 15-Aug-06 15:11		FS — 10	BN 101 SL 2590/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS±0.1 FR 20000 MB 30 DL -33 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1020		TS 12 B PD: 20109-060 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.4 FMX= 68 AMX= 159 EMX= 0.3 MEX= 133 FVP= 1.02			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 20109 CALIBRATION FACTOR: 1020 GN RAK (*5000): DATE: 15-AUG-06 PDA OPERATOR: <i>[Signature]</i>			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		OP: alex [ver:4.05]			

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->