


QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

Pile Dynamics 05-Feb-10 13:21 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -29 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1040	FS 10 BN 673 SL 2936/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 TB 8.0 T1 9.4 B PD: 20114.060 2L/C 4.7 UA 1000 UE 1022 LP 0.00 ft LI 1.0
--	--

ACCEPT SQ-OFF FL-OFF PR-OFF  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	UMX= 4.6 FMX= 62 AMX= 139 EMX= 0.2 MEX= 121 FVP= 0.99 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 20114 CALIBRATION FACTOR: 1040 G/V PAK (*5000)+ DATE: 05-FEB-10 PDA OPERATOR:  DP: alex [ver:4.05]
--	---

<-AT:PIEZORESISTIVE

[AT:PIEZOELECTRIC->