

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 27-Sep-06 09:34		FS — 10	BN 271 SL 2605/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -41 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 990					
TS 12 TB 8.0		B PD: 20125-060 TI 9.4 2L/C 4.7 VA 1000 UE 1022 LP 0.00 ft LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 3.7 FMX= 57 AMX= 120
EMX= 0.2 MEX= 111 FUP= 1.01



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 20125

CALIBRATION FACTOR: 990 61V

PAK (*5000): DATE: 28-SEP-06

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

[AT:PIEZOELECTRIC->