

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 24-Feb-09 12:09	FS — 10	BN 114 SL 3/ 3440/ 2	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30				
DL -22 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1015	TS 12 TB 8.0	B PD: 20332-060 T1 10.0 2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.2 FMX= 66 AMX= 159
EMX= 0.3 MEX= 129 FUP= 0.99



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 20332

CALIBRATION FACTOR: 1015 G/v

PAK (*5000) DATE: 24-FEB-09

PDA OPERATOR:

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->