

QBTB: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 09-Feb-11 09:12		FS —	BN 848	PJ: sn	TG F2 -- US
		10	SL 2906/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16862 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1		TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
FR 20000 MB 30					
DL -40					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 1050					

ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 3.9 FMX= 60 AMX= 139 EMX= 0.2 MEX= 117 FUP= 0.99	
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable	
		SERIAL NUMBER: 20337	
		CALIBRATION FACTOR: 1050 G/V	
		PAK (*5000): DATE: 09-FEB-11	
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		PDA OPERATOR: <i>[Signature]</i>	
<-AT:PIEZORESISTIVE		OP: alex [ver:4.05]	
		AT:PIEZOELECTRIC->	