

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

File Dynamics 02-Nov-06 11:03	FS — 10	BN 25 SL 2585/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30				
DL -17 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1030				
TS 12 TB 8.0	B PD: 20342-060 T1 9.6 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0		

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.2 FMX= 63 AMX= 149 EMX= 0.3 MEX= 123 FVP= 1.00
-----------------------------	--



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 20342

CALIBRATION FACTOR: 1030 G/V

PAK (*5888): DATE: 02-NOV-06

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

[AT:PIEZOELECTRIC->