

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 26-Feb-09 14:04		FS — 10	BN 244 SL 2753/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft	AR 1.7 in2	EM 30000 Ksi	SP 0.492 K/ft3	WS 16810 ft/s	WC 16862 ft/s
JC 0.40	FM 1.00	UM 1.00			
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL -33					
UT -1					
PK 1 TM-PEAK					
F1 500					
F2 213					
A1 999					
A2 1055					
TS 12		B PD: 20360-060		LP 0.00 ft	
TB 8.0		T1 9.4		2L/C 4.7 VA 1000	
		VE 1022		LI 1.0	

 contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCEPT SQ-OFF FL-OFF PR-OFF VMX= 3.9 FMX= 60 AMX= 129 EMX= 0.2 MEX= 117 FVP= 0.99 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 20360 CALIBRATION FACTOR: 1055 G/v PAK (*5000): DATE: 26-FEB-09 PDA OPERATOR: <i>[Signature]</i>

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->