

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 10-Oct-06 10:32		FS 10	BN 98 SL 2585/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -26 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1000		TS 12 TB 8.0	B PD: 20363-060 T1 9.5 2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.0 FMX= 62 AMX= 149
EMX= 0.3 MEX= 121 FVP= 0.97



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 20363

CALIBRATION FACTOR: 1000 G/V

PAK < *5000 > DATE: 10-06T-06

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.03]

[AT:PIEZOELECTRIC->