

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics
13-Oct-10 12:38FS —
10BN 17
SL 2844/ 3440/ 99PJ: sn
PN: HOPBARTG F2 -- US
A2 F2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 16862 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS:30.1
FR 20000 MB 30DL -27
UT -1
PK 1 TM-PEAKF1 500
F2 213
A1 999
A2 1025TS 12 B PD: 20982 LP 0.00 ft
TB 8.0 T1 9.6 2L/C 4.7 VA 1000 UE 1022 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916VMX= 4.1 FMX= 63 AMX= 159
EMX= 0.3 MEX= 123 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 20982

CALIBRATION FACTOR: 1025 G/v

PAK (*5000): DATE: 13-OCT-10

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

>PIEZOELECTRIC<