

QBTA: DN [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

<b>Pile Dynamics</b> 14-Mar-12 11:01		FS — 10	BN 5365 SL 207/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN <del>KIPS/IN</del> FR 20000 MB 30  DL -40 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1020	TS 12 TB 8.0	B PD: 40520-075 T1 9.6 2L/C 4.7 VA 1000	VE 1022	LP 0.00 ft LI 1.0	

<input type="checkbox"/> ACCEPT	<input type="checkbox"/> SQ-OFF	<input type="checkbox"/> FL-OFF	<input type="checkbox"/> PR-OFF	VMX= 4.1 FMX= 62 AMX= 169 EMX= 0.2 MEX= 121 FVP= 1.00
---------------------------------	---------------------------------	---------------------------------	---------------------------------	--



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 40520  
 CALIBRATION FACTOR: 1020 G/v  
 PAK (\*5000): DATE: 14-MAR-12  
 PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: ALEX [ver:4.05]

ATPIEZOELECTRIC->