

Pile Dynamics 14-Mar-12 11:08	FS — 10	BN 5368 SL 207 / 3440 / 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS=30.1 FR 20000 MB 30						
DL -24 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1050						
TS 12 TB 8.0					B PD: 40521-075 T1 9.6 2L/C 4.7 UA 1000	LP 0.00 ft UE 1022 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.0 FMX= 61 AMX= 159
EMX= 0.2 MEX= 119 FUP= 1.00



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 40521

CALIBRATION FACTOR: 1050 G/v

PAK (*5880): DATE: 14-MAR-12

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: ALEX [ver:4.05]

AT:PIEZOELECTRIC->