

File Dynamics 17-May-12 14:23 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS 30.0 FR 20000 MB 30 DL -26 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1060	FS 10 BN 793 SL 3239/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 40634-075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 VA 1000 VE 1022 LI 1.0
---	---

ACCEPT SQ-OFF FL-OFF PR-OFF contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.0 FMX= 61 AMX= 149 EMX= 0.2 MEX= 119 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 40634 CALIBRATION FACTOR: 1060 G/v PAK (*5000): DATE: 17-may-12 PDA OPERATOR: <i>[Signature]</i>
--	---

←-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC-→